

IN THE CLAIMS:

CLAIM 1(ORIGINAL). A nozzle for dispensing a liquid, such as an elastomer for use with a rotational casting apparatus used to coat a body, comprising:

an interior flow passageway through which liquid flows;

said interior flow passageway defining a straight longitudinal axis along the length thereof, and having an inlet section, an intermediate section, and an outlet opening;

said intermediate section comprising a plurality of different portions, each said portion having a cross-sectional shape along said longitudinal axis different from a cross sectional shape of another of said plurality of different portions; each said cross-sectional shape being defined in a plane transverse to said longitudinal axis;

each said cross-sectional shape of each of said plurality of different portions defining a cross-sectional area substantially equal to the cross-sectional area of another said cross-sectional shape of said plurality of different cross-sectional shapes;

said outlet opening having a substantially elongated-like shape and having a cross-sectional area greater than said cross-sectional area of each said cross-sectional shape of said plurality of different cross-sectional shapes, whereby substantial laminar flow through said intermediate section and substantial equality of dwell-time of each hypothetical section of flowing liquid in said intermediate section occurs.

CLAIM 2(ORIGINAL). The nozzle according to claim 1, wherein said inlet section of said interior passageway comprises laminar-flow tubular section for ensuring laminar flow therein.

CLAIM 3(ORIGINAL). The nozzle according to claim 2, wherein said laminar-flow tubular section for ensuring laminar flow comprises a venturi-flow tubular portion, said venturi-flow tubular portion having an end-cross-section having a cross-sectional area substantially equal to said cross-sectional area of each of said plurality of different cross-sectional shapes.

CLAIM 4(ORIGINAL). The nozzle according to claim 1, wherein said plurality of different portions comprises a first series of substantially circular cross sections and second series of substantially ellipse-like cross sections.

CLAIM 5(ORIGINAL). The nozzle according to claim 4, wherein said plurality of different portions further comprises a third series of substantially elongated slot-like cross sections.

CLAIM 6(ORIGINAL). The nozzle according to claim 5, wherein at least some of said third series of substantially elongated slot-like cross sections are an oval-of-Cassini-like shape.

CLAIM 7(ORIGINAL). The nozzle according to claim 6, wherein said outlet opening is an oval-of-Cassini-like shape.

CLAIM 8(ORIGINAL). The nozzle according to claim 1, wherein said outlet opening is an oval-of-Cassini-like shape.

CLAIM 9(ORIGINAL). The nozzle according to claim 1, wherein said outlet opening comprises a cross-sectional area at least twice as great as said cross-sectional area of each said cross-sectional shape of said plurality of different cross-sectional shapes.

CLAIM 10(ORIGINAL). The nozzle according to claim 1, wherein said plurality of different portions shapes comprises a first series of substantially circular cross-sectional shapes, and a second series of substantially elongated cross-sectional shapes.

CLAIM 11(ORIGINAL). The nozzle according to claim 10, wherein at least some of said second series of substantially elongated cross-sectional shapes are an oval-of-Cassini-like shape.

CLAIM 12(ORIGINAL). The nozzle according to claim 11, wherein said outlet opening is an oval-of-Cassini-like shape.

CLAIM 13(ORIGINAL). The nozzle according to claim 12, wherein said outlet opening comprises a cross-sectional area at least twice as great as said cross-sectional area of said second series of cross-sectional shapes.

CLAIM 14(ORIGINAL). The nozzle according to claim 10, wherein each said cross section of said second series of substantially elongated cross-sectional shapes comprises a horizontal x-coordinate dimension and a vertical y-coordinate direction; each said cross section of said third

series of elongated cross- section shapes having a x-y product different from that of any other respective said cross section of said third series.

CLAIM 15(ORIGINAL). The nozzle according to claim 1, wherein said inlet section of said interior passageway comprises a laminar-flow tubular section for ensuring laminar flow therein; said laminar-flow tubular section comprising a venturi-flow tubular portion, said venturi-flow tubular portion having a circular end-cross-section having a cross-sectional area substantially equal to said cross-sectional area of each of said plurality of different cross-sectional shapes.

CLAIM 16(CANCELLED).

CLAIM 17(CANCELLED).

CLAIM 18(ORIGINAL). A dispensing nozzle for dispensing fluid comprising:

an unbranched interior flow passageway through which the liquid flows;

said interior flow passageway defining a straight longitudinal axis along the length thereof and having an inlet section, an intermediate section and an outlet;

said intermediate section comprising a plurality of different cross-sectional shapes along said longitudinal axis; each said cross-sectional shape being defined in a plane transverse to said longitudinal axis;

each said cross-sectional shape defining a cross-sectional area substantially equal to the cross-sectional area of another said cross-sectional shape.

CLAIM 19(ORIGINAL). The dispensing nozzle according to claim 18, wherein said outlet has a shape similar to the shape of the last cross-sectional shape of said intermediate section adjacent thereto, whereby substantial laminar flow through said intermediate section and substantial equality of dwell-time of each hypothetical section of flowing liquid in said intermediate section occurs; said plurality of different cross sections comprising a first series of substantially circular cross-sectional shapes, a second series of substantially ellipse-like cross-sectional shapes, and a third series of substantially elongated cross-sectional shapes.

CLAIM 20(PREVIOUSLY PRESENTED). A dispensing nozzle comprising:

an interior flow passageway through which fluid flows;

said interior flow passageway defining a longitudinal axis along the length thereof, and having an inlet section, an intermediate section, and an outlet opening;

said intermediate section comprising a plurality of different cross-sectional shapes along said longitudinal axis; each said cross-sectional shape being defined in a plane transverse to said longitudinal axis; and

each said cross-sectional shape defining a cross-sectional area substantially equal to the cross-sectional area of every other said cross-sectional shape of said plurality of different cross-sectional shapes.